



**AFCTN Test Report
93-036**

**AFCTB-ID
92-084**



Raster Transfer Test

Using:



Image Memory Systems' Data



MIL-R-28002A (Raster)

Quick Short Test Report

25 November 1992

19960822 044


Prepared for
Electronic Systems Center

DTIC QUALITY INSPECTED 3



DISTRIBUTION STATEMENT A
Approved for public release;
Distribution Unlimited

DISCLAIMER NOTICE



THIS DOCUMENT IS BEST
QUALITY AVAILABLE. THE COPY
FURNISHED TO DTIC CONTAINED
A SIGNIFICANT NUMBER OF
PAGES WHICH DO NOT
REPRODUCE LEGIBLY.

Raster Transfer Test
Using:
Image Memory Systems' Data

MIL-R-28002A (Raster)

Quick Short Test Report

25 November 1992

Prepared By
Air Force CALS Test Bed
Wright-Patterson AFB, OH 45433

AFCTB Contact
Gary Lammers
(513) 427-2295

AFCTN Contact
Mel Lammers
(513) 427-2295

DISCLAIMER

This document was prepared as an account of the work sponsored by the Air Force. Neither the United States Government, the Air Force, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, nor represents that its use would not infringe on privately owned rights. Reference herein to any specific commercial products, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the Air Force. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or the Air Force, and shall not be used for advertising or product endorsement purposes.

Available to the public from the
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Rd.
Springfield, VA 22161

This report and those involved in its preparation do not endorse any product, process, or company stated herein. Use of these means by anyone does not imply certification by the Air Force CALS Test Network (AFCTN).

Contents

1.	Introduction.....	1
1.1	Background.....	1
1.2	Purpose.....	2
2.	Test Parameters.....	3
3.	1840A Analysis.....	5
3.1	External Packaging.....	5
3.2	Transmission Envelope.....	5
3.2.1	Tape Formats.....	5
3.2.2	Declaration and Header Fields.....	6
4.	IGES Analysis.....	7
5.	SGML Analysis.....	7
6.	Raster Analysis.....	7
7.	CGM Analysis.....	8
8.	Conclusions and Recommendations.....	9
9.	Appendix A - Tape Tool Report Logs.....	10
9.1	Tape Catalog.....	10
9.2	Tape Evaluation Log.....	11
9.3	Tape File Set Validation Log.....	15
10.	Appendix B - Detail Raster Analysis.....	18
10.1	File D001R005.....	18
10.1.1	Output IGESView.....	18
10.1.2	Output Preview.....	19

10.2 File D010R001.....	20
10.2.1 Output IGESView.....	20
10.3 File D018R013.....	21
10.3.1 Output IGESView.....	21
10.4 File D029R004.....	22
10.4.1 Output IGESView.....	22
10.4.2 Output Ventura Publisher.....	23

1. Introduction

1.1 Background

The Department of Defense (DoD) Air Force Continuous Acquisition and Life-Cycle Support (CALS) Test Network (AFCTN) is conducting tests of the military standard for the Automated Interchange of Technical Information, MIL-STD-1840A, and its companion suite of military specifications. The AFCTN is a DoD sponsored confederation of voluntary participants from industry and government managed by the Electronic Systems Center (ESC).

The primary objective of the AFCTN is to evaluate the effectiveness of the CALS standards for technical data interchange and to demonstrate the technical capabilities and operational suitability of those standards. Two general categories of tests are performed to evaluate the standards; formal and informal.

Formal tests are large and comprehensive, which follow a written test plan, required specific authorization from the DoD, and may take months to prepare, execute, and report.

Informal tests are quick and short, used by the AFCTN technical staff, to broaden the testing base. They include representative samples of the many systems and applications used by AFCTN participants. They also allow the AFCTN staff to gain feedback from many industry and government interpretations of the standards, to increase the base of participation in the CALS initiative, and respond to the many requests for help that come from participants. Participants take part voluntarily, benefit by receiving and evaluation of their latest implementation (intrepretation) of the standards, interact with the AFCTN technical staff, gain experience using the standards, and develop increased confidence in them. The results of informal tests are reported in Quick Short Test Reports (QSTRs) that briefly summarize the standard(s) tested, the hardware and software used, the nature of the test, and the results.

1.2 Purpose

The purpose of the informal test reported in this QSTR was to analyze Image Memory Systems' interpretation and use of the CALS standards in transferring raster data. Image Memory Systems used its CALS Technical Data Interchange System to produce data in accordance with the standards and delivered it to the AFCTN technical staff on a 9-track magnetic tape.

2. Test Parameters

Test Plan: AFCTB 92-084

Date of
Evaluation: 25 November 1992

Evaluator: George Elwood
Air Force CALS Test Bed
Dpt 2 HQ ESC/ENCP
4027 Colonel Glenn Hwy
Suite 200
Dayton, OH 45431-1672

Data
Originator: John Pugnale
Image Memory Systems
6000 Webster Street
Dayton, OH 45414

Data
Description: Technical Manual Test
53 Document Declaration files
71 Raster files

Data
Source System:

Raster

HARDWARE

Unknown

SOFTWARE

Unknown

Evaluation Tools Used:

MIL-STD-1840A (TAPE)

SUN 3/280

AFCTN Tapetool v1.2.8 UNIX

MIL-R-28002 (Raster)

SUN SparcStation 2

ArborText g42tiff

AFCTN validg4

AFCTN calstb.475

IGES Data Analysis (IDA) IGESView v3.0

Island Graphics IslandPaint v3.0

Cheetah

Inset Systems HiJaak v2.02

Corel Ventura Publisher

Standards

Tested:

MIL-STD-1840A

MIL-R-28002A

3. 1840A Analysis

3.1 External Packaging

The tape arrived at the Air Force CALS Test Bed (AFCTB) enclosed in a box in accordance with ASTM D 3951. The exterior of the box was marked with the magnetic tape warning label, as required by MIL-STD-1840A, para. 5.3.1.3.

The tape was enclosed in a barrier bag as required by MIL-STD-1840A, para. 5.3.1.2. Inspection of the tape reel showed the label indicating the recording density, as required by MIL-STD-1840A, para. 5.3.1. Enclosed in the box was a packing list showing all files recorded on the tape.

3.2 Transmission Envelope

The 9-track tape received by the Air Force CALS Test Bed contained MIL-STD-1840A files. The files were named per the standard conventions.

3.2.1 Tape Formats

The 1840A Tape was run through the AFCTB Tapetool v1.2.8 utility. While evaluating the contents of the tape labels, 557 errors and 207 notes were reported. An additional 57 notes were reported during the evaluation of the Tape Catalog. All of the errors are shown in Appendix A, Sections One and Two.

Many of the errors related to the tape label Record Length field for Type D files. Type D files contain variable length records that do not span blocks. All of the Type D files written on the tape were flagged with an illegal value for Record Length. The DOXX files were expected to be Type D according to MIL-STD-1840A. The AFCTN Tapetool Software is expecting a value of 260 in the Record Length field but encountered a record length 256. MIL-STD-1840A para. 5.2.1.3 requires the variable record size be a maximum of 256 bytes. ANSI X3.27 para. 7.2.3 further states that the length of a Record Control Word (RCW) must be included in a Measured

Data Unit (MDU) record length computation. This adds four bytes to the 256 for an MDU total of 260 bytes. ANSI X3.27 para. 8.5.2.6 states that the Record Length field for Type D files shall contain the maximum length of an MDU. While MIL-STD-1840A permits variable length records, some software programs are sensitive to the number 260 because it is used to limit the record size when unblocking data. Some systems need this value to declare the maximum allowable record size as an attribute of a file when it is created.

A note was reported on the tape label version. MIL-STD-1840A permits the use of both versions three and four. The use of the most current standard should be used and noted.

All files were reported with characters in a reserved block defined by ANSI 3.27. This error was reported in both the HDR2 and EOF2 files.

HDR2D0204800256

B

00

*** ERROR (ANSI X3.27; 8.5.1.1) - Columns 53-80 are reserved for future standardization and must be spaces.

Most of the Raster files had an incomplete last block note. This would indicate that the last block of data was not padded to the required length. This could result in the last block of data being deleted when read by some tape drives.

*** NOTE - Last block was incomplete. Short blocks are prone to be interpreted as noise by some tape drives.
Tape Label => 2048, Actual => 640, Block Number => 23

3.2.2 Declaration and Header Fields

In the Document Declaration Files and data file headers, 354 errors and 354 notes were reported. In all Document Declaration files, an Invalid change level was flagged. MIL-STD-1840A, para. 5.1.1.2 shows the change level as "ORIGINAL". The value for chglvl is either the word "ORIGINAL" or the revision level, change level, and then the change date.

chglvl: A

- *** ERROR (MIL-STD-1840A; 5.1.1.2) - Invalid change level encountered.
- *** NOTE (MIL-STD-1840A; 5.1.1.2) - Change level should be the word ORIGINAL or a Revision Number followed by a Change Level Number followed by a Change Level Date. They should be separated by a comma or space.

Errors were also reported with record doctyp. No value was given for this record. The record must contain a value of "NONE".

doctyp:

- *** ERROR (MIL-STD-1840A; 5.1.1.2) - Space missing after Document Declaration header field.
- *** ERROR (MIL-STD-1840A; 5.1.1.2) - Value missing after Document Declaration header field.
- *** NOTE - The header record will be given the value NONE.
- *** NOTE - Correction made in new Document Declaration Header File.

All Raster file headers reported an error with the srcdocid record. MIL-STD-1840A does not permit more than one space after the colon. All of these files contained multiple spaces.

- srcdocid: A3023860 80063 A 00010007UDUHN0001 A
- *** ERROR (MIL-STD-1840A; 5.1.4) - Value contains leading spaces.
 - *** NOTE - Correction made in new %s Header File.

4. IGES Analysis

No Initial Graphics Exchange Specification (IGES) files were included on the tape.

5. SGML Analysis

No Standard Generalized Markup Language (SGML) files were included on the tape.

6. Raster Analysis

Because of the number of Raster files on the tape, a selection was made for closer inspection. A larger selection was made and checked using the AFCTN *validg4* utility. All of the selected files were reported as meeting the CALS MIL-R-28002A specification.

The six selected files were imported into the AFCTN *calstb.475*. No problems were reported. The files appear to be scanned straight. Minor orphan pixels were noted on some of the images.

The files were converted using ArborText's *g42tiff* utility. No problems were encountered. The resulting files were imported into Island Graphics' *IslandPaint*, displayed and printed.

The files were converted to an IMG format using Inset Systems' *HiJaak*. No problems were reported. The resulting files were imported into Corel's *Ventura Publisher* and printed.

The files were read into IDA's *IGESView* with CALS Raster options. No errors were reported. The hard copies of this process are included in the Appendix.

The files were converted using Rosetta Technologies' *Prepare* without a reported problem. The resulting files were read into *Preview*, displayed and printed.

The Raster files meet the CALS MIL-R-28002A specification.

7. CGM Analysis

No Computer Graphic Metafile (CGM) files were included on the tape.

8. Conclusions and Recommendations

In summary, the physical structure of the tape from Image Memory Systems did not meet the CALS MIL-STD-1840A requirements. There were numerous reported errors with the tape labels and CALS headers.

The Raster files on the tape meet the CALS MIL-R-28002A specification.

Due to the physical structure errors, the tape from Image Memory Systems does not meet the CALS MIL-STD-1840A requirements.

9. Appendix A - Tapetool Report Logs

9.1 Tape Catalog

Air Force CALS Test Network Catalog Evaluation - Version 1.2; Release Number 8

Standards referenced:

- MIL-STD-1840A (1987) - Automated Interchange of Technical Information
- ANSI X3.27 (1987) - File Structure and labeling of Magnetic Tapes
for Information Interchange
- ANSI X3.4 (1986) - Coded Character Sets - 7 Bit ASCII

Wed Nov 25 09:06:32 1992

MIL-STD-1840A File Catalog

File Set Directory: /cals/tapetool8/Set116

Page: 1

File Name	File Type	Record Format/ Length	Block Length/Total	Selected/ Extracted
D001	Document Declaration	D/00256	02048/000001	Extracted
*** NOTE (MIL-STD-1840A; 5.2.1.3) - Unexpected maximum variable record size encountered. Header => 256, Expected => 260				
*** NOTE (ANSI X3.27; 8.5.2.6) - Record Length for Recording Format Type D shall be the maximum length of a Measured Data Unit (MDU).				
*** NOTE (ANSI X3.27; 7.2.3) - A variable length record shall be contained in an MDU. An MDU consists of a four byte Record Control Word (RCW) followed immediately by the variable record.				
*** NOTE (ANSI X3.4) - A Record Control Word shall consist of four characters that express the sum of the lengths of the RCW and the variable record.				
D002	Document Declaration	D/00256	02048/000001	Extracted
*** NOTE (MIL-STD-1840A; 5.2.1.3) - Unexpected maximum variable record size encountered. Header => 256, Expected => 260				

<<<<< PART OF LOG REMOVED HERE >>>>>

D001R001	Raster	F/00128	02048/000017	Extracted
D001R002	Raster	F/00128	02048/000017	Extracted

<<<<< PART OF LOG REMOVED HERE >>>>>

D050R001 Raster F/00128 02048/000023 Extracted

Catalog Process terminated with 0 error(s), 0 warning(s), and 53 note(s).

9.2 Tape Evaluation Log

Air Force CALS Test Network Tape Evaluation - Version 1.2; Release Number 8

Standards referenced:

ANSI X3.27 (1987) - File Structure and labeling of Magnetic Tapes
for Information Interchange

ANSI X3.4 (1986) - Coded Character Sets - 7 Bit ASCII

Wed Nov 25 09:02:41 1992

ANSI Tape Import Log

Allocating tape drive /dev/rmt0...

/dev/rmt0 allocated.

VOL1000001

MAGNAVOX REGEN

3

Label Identifier: VOL1

Volume Identifier: 000001

Volume Accessibility:

Owner Identifier: MAGNAVOX REGEN

Label Standard Version: 3

*** NOTE (ANSI X3.27; 8.3.1.8) - The Label Standard Version
should be 4 to represent the current level of ANSI X3.27.

HDR1D001

000001000100010000 92328 00000 000000

Label Identifier: HDR1

File Identifier: D001

File Set Identifier: 000001

File Section Number: 0001

File Sequence Number: 0001

Generation Number: 0000

Generation Version Number:

Creation Date: 92328

Expiration Date: 00000

File Accessibility:

Block Count: 000000

Implementation Identifier:

HDR2D0204800256

B

00

Label Identifier: HDR2
Recording Format: D
Block Length: 02048
Record Length: 00256
Offset Length: 0

*** ERROR (ANSI X3.27; 8.5.1.1) - Columns 53-80 are reserved
for future standardization and must be spaces.

***** Tape Mark *****

Actual Block Size Found = 2048 Bytes.

Number of data blocks read = 1.

***** Tape Mark *****

EOF1D001

000001000100010000

92328 00000 000001

Label Identifier: EOF1
File Identifier: D001
File Set Identifier: 000001
File Section Number: 0001
File Sequence Number: 0001
Generation Number: 0000
Generation Version Number:
Creation Date: 92328
Expiration Date: 00000
File Accessibility:
Block Count: 000001
Implementation Identifier:

EOF2D0204800256

B

00

Label Identifier: EOF2
Recording Format: D
Block Length: 02048
Record Length: 00256
Offset Length: 0

*** ERROR (ANSI X3.27; 8.5.1.1) - Columns 53-80 are reserved
for future standardization and must be spaces.

***** Tape Mark *****

<<<< PART OF LOG FILE REMOVED HERE >>>>

***** Tape Mark *****

HDR1D050R001 000001000102780000 92328 00000 000000

Label Identifier: HDR1
File Identifier: D050R001
File Set Identifier: 000001
File Section Number: 0001
File Sequence Number: 0278
Generation Number: 0000
Generation Version Number:
Creation Date: 92328
Expiration Date: 00000
File Accessibility:
Block Count: 000000
Implementation Identifier:

HDR2F0204800128 B 00

Label Identifier: HDR2
Recording Format: F
Block Length: 02048
Record Length: 00128
Offset Length: 0

*** ERROR (ANSI X3.27; 8.5.1.1) - Columns 53-80 are reserved
for future standardization and must be spaces.

***** Tape Mark *****

Actual Block Size Found = 2048 Bytes.

*** NOTE - Last block was incomplete. Short blocks are
proned to be interpreted as noise by some tape drives.
Tape Label => 2048, Actual => 640, Block Number => 23

Number of data blocks read = 23.

***** Tape Mark *****

EOF1D050R001 000001000102780000 92328 00000 000023

Label Identifier: EOF1
File Identifier: D050R001

File Set Identifier: 000001
File Section Number: 0001
File Sequence Number: 0278
Generation Number: 0000
Generation Version Number:
Creation Date: 92328
Expiration Date: 00000
File Accessibility:
Block Count: 000023
Implementation Identifier:

EOF2F0204800128

B

00

Label Identifier: EOF2
Recording Format: F
Block Length: 02048
Record Length: 00128
Offset Length: 0

*** ERROR (ANSI X3.27; 8.5.1.1) - Columns 53-80 are reserved
for future standardization and must be spaces.

***** Tape Mark *****

***** Tape Mark *****

End of Volume 000001

End Of Tape File Set

Deallocating /dev/rmt0...

Tape Import Process terminated with 557 error(s), 0 warning(s),
and 207 note(s).

9.3 Tape File Set Validation Log

Air Force CALS Test Network File Set Evaluation - Version 1.2; Release Number 8
Standards referenced:

MIL-STD-1840A (1987) - Automated Interchange of Technical Information

MIL-R-28002 (1989) - Raster Graphics Representation In Binary
Format, Requirements For

Wed Nov 25 09:06:35 1992

MIL-STD-1840A File Set Evaluation Log

File Set: Set116

Found file: D001

Extracting Document Declaration Header Records...

Evaluating Document Declaration Header Records...

srcsys: Magnavox Electronic Systems Co, 1313 Production Road, Ft Wayne, IN 46808, Cage
37695

srcdocid: A3023860

srcrelid: DAAB07-84-C-D001

chglvl: A

*** ERROR (MIL-STD-1840A; 5.1.1.2) - Invalid change level encountered.

*** NOTE (MIL-STD-1840A; 5.1.1.2) - Change level should be the word ORIGINAL or
a Revision Number followed by a Change Level Number followed by
a Change Level Date. They should be separated by a comma or space.

dteisu: 19921120

dstsys: U S Army Communications-Electronics Command, Ft Monmouth, NJ 07705, Cage Code

dstdocid: A3023860

dstrelid: DAAB07-84-C-D001

dtetrm: 19921120

dlvacc: SLIN 0005AL, CDRL 17-11, DI-E-7031, W/ADD,19AUG82&W/Supp,21Oct82

filcnt: R7

ttlcls: Unclass

doccls: Unclass

doctyp:

*** ERROR (MIL-STD-1840A; 5.1.1.2) - Space missing after Document Declaration
header field.

*** ERROR (MIL-STD-1840A; 5.1.1.2) - Value missing after Document Declaration
header field.

*** NOTE - The header record will be given the value NONE.

*** NOTE - Correction made in new Document Declaration Header File.

doctl: SEMICONDUCTOR DEVICE,DIODE - LIGHT EMITTING

3 error(s), 0 warning(s), and 3 note(s) were encountered

in Document Declaration File D001.

Found file: D001R001
Renaming file from => /cals/tapetool8/Set116/D001R001
to => /cals/tapetool8/Set116/D001/D001R001
Extracting Raster Header Records...
Evaluating Raster Header Records...

srcdocid: A3023860 80063 A 00010007UDUHN0001 A
*** ERROR (MIL-STD-1840A; 5.1.4) - Value contains leading spaces.
*** NOTE - Correction made in new %s Header File.
dstdocid: NONE
txtfilid: NONE
figid: NONE
srcgph: NONE
doccls: NONE
rtype: 1
rorient: 000,270
rpelcnt: 001680,002224
rdensty: 0200
notes: NONE

1 error(s), 0 warning(s), and 1 note(s) were encountered
in Raster File D001R001.

Saving Raster Header File: D001R001_HDR
Saving Raster Data File: D001R001_GR4

Found file: D001R002
Renaming file from => /cals/tapetool8/Set116/D001R002
to => /cals/tapetool8/Set116/D001/D001R002
Extracting Raster Header Records...
Evaluating Raster Header Records...

srcdocid: A3023860 80063 A 00020007UDUHN0002 A
*** ERROR (MIL-STD-1840A; 5.1.4) - Value contains leading spaces.
*** NOTE - Correction made in new %s Header File.
dstdocid: NONE
txtfilid: NONE
figid: NONE
srcgph: NONE
doccls: NONE
rtype: 1
rorient: 000,270
rpelcnt: 001664,002224
rdensty: 0200
notes: NONE

1 error(s), 0 warning(s), and 1 note(s) were encountered
in Raster File D001R002.

Saving Raster Header File: D001R002_HDR

Saving Raster Data File: D001R002_GR4

<<<<< PART OF LOG REMOVED HERE >>>>>

Found file: D050R001

Renaming file from => /cals/tapetool8/Set116/D050R001

to => /cals/tapetool8/Set116/D050/D050R001

Extracting Raster Header Records...

Evaluating Raster Header Records...

srcdocid: MPA37659 80063 A 00010001UDUHN0001 D

*** ERROR (MIL-STD-1840A; 5.1.4) - Value contains leading spaces.

*** NOTE - Correction made in new %s Header File.

dstdocid: NONE

txtfilid: NONE

figid: NONE

srcgph: NONE

doccls: NONE

rtype: 1

rorient: 000,270

rpelcnt: 006608,004400

rdensty: 0200

notes: NONE

1 error(s), 0 warning(s), and 1 note(s) were encountered
in Raster File D050R001.

Saving Raster Header File: D050R001_HDR

Saving Raster Data File: D050R001_GR4

Evaluating numbering scheme...

No errors were encountered during numbering scheme evaluation.

Numbering scheme evaluation complete.

Checking file count...

No errors were encountered during file count verification.

File Count verification complete.

A total of 4 error(s), 0 warning(s), and 4 note(s) were
encountered in Document D050.

A grand total of 354 error(s), 0 warning(s), and 354 note(s) were
encountered in this File Set.

MIL-STD-1840A File Set Evaluation Complete.

10. Appendix B - Detail Raster Analysis

10.1 File D001R005

10.1.1 Output IGESView

3.0	2.2	5.0	565	2.2	3.0	200	45
MAX	TYP	MIN	REF	MIN	TYP	REF	REF
V_F	V_A	V_R	λ_{PK}	I_V	T_S	C	
FORWARD VOLTAGE $I_F=20\text{ mA}$	REVERSE VOLTAGE $I_R=100\text{ }\mu\text{A}$	PEAK WAVELENGTH	LUMINOUS INTENSITY $I_F=20\text{ mA}$	RISE AND FALL TIME	CAPACITANCE $V_F=0, f=1\text{ MHz}$		
V	V	nm	mcd	ns	pF		
ELECTRICAL/OPTICAL CHARACTERISTICS AT $T_A = +25^\circ\text{C}$							

TABLE II

105	35	1	-50 TO +100
POWER DISSIPATION DERATE LINEARLY FROM +25°C AT 1.14 mW/°C	AVERAGE FORWARD CURRENT	PEAK OPERATING FORWARD CURRENT 1 μs PULSE WIDTH 35 DUTY CYCLE	OPERATING AND STORAGE TEMPERATURE RANGE
mW	mA	A	°C
ABSOLUTE MAXIMUM RATINGS			

TABLE I

DAAB07-84-C-D001

SIZE	FROM NO.	DRWG. NO.
A	80063	A3023860
SCALE	4/1	LTR - SHEET 5

DAAB-ED Form 01-1 1 Jul 82

DAAB-PN 1467-1-82

10.1.2 Output Preview

APPLICATION		REVISIONS	
NEXT ASSY	USED ON	LTR	DESCRIPTION
A3024804	DLA3024804	—	ORIGINAL RELEASE
A3024829	DLA3024829		
		A	REVISED APPL, PARA 2.3, 5.2 AND 7.1. ADDED PARA 3.5. FIG 1, ADDED UNITS CALLOUT. ECN A94486 P.2-1109 8/7/11

NOTE: DATA MARKED WITH AN ASTERISK (*) IS PECULIAR TO A PRIOR MANUFACTURER. IT DOES NOT TAKE PRECEDENCE OVER ANY OTHER DATA ON THIS DRAWING. AND IS NOT CONTRACTUALLY BINDING ON EITHER THE CONTRACTOR OR THE GOVERNMENT.

DAAB07-84-C-D001

SELECTED ITEM DRAWING

REVISION	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
SHEET	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20


THIS DOCUMENT HAS BEEN PURCHASED BY THE GOVERNMENT AND MAY BE REPRODUCED AND USED IN CONNECTION WITH ANY GOVERNMENT PROCUREMENT OR MAINTENANCE OPERATION	-HAGIEC-		U.S. ARMY COMMUNICATIONS - ELECTRONICS COMMAND FORT MONMOUTH, NEW JERSEY 07703	
	DAAB07-84-C-D001		SEMICONDUCTOR DEVICE, DIODE - LIGHT EMITTING	
	DRAWN T. DeROSE			
	CHECKED R. Thibault			
	CECOM			
REVIEWED ED-RT(RG)	SIZE A	FSCM NO. 80063	DWG. NO. A3023860	
APPROVED ED-RO(EL)	SCALE 4/1	SHEET 1 OF 7		
DATE 92-09-08				

WHEN REFERRING TO THIS DRAWING STATE DRAWING NO., APPLICABLE ISSUE LETTER IF ANY AND DATE

10.2.1 Output IGESView

[illegible]

10.3.1 Output IGESView



10.4 File D029R004

10.4.1 Output IGESView

3.4.2.2 SOLDERABILITY: SOLDERABILITY TEST PER MIL-T-23648 IS APPLICABLE.

3.4.2.3 RESISTANCE TO SOLDERING HEAT: WHEN TESTED IN ACCORDANCE WITH MIL-T-23648, MAXIMUM CHANGE IN ZERO POWER RESISTANCE SHALL BE $\pm 1\%$.

3.4.3 MARKING: UNITS SHALL BE IDENTIFIED BY MARKING ON THE UNIT PACKAGE IN ACCORDANCE WITH MIL-STD-1285, METHOD 1. THE MARKING SHALL INCLUDE MANUFACTURER'S NAME AND CODE SYMBOL, MANUFACTURER'S PART NUMBER, DATE CODE AND ZERO POWER RESISTANCE.

4.0 QUALITY ASSURANCE PROVISIONS

4.1 RESPONSIBILITY FOR INSPECTION: THE MANUFACTURER IS RESPONSIBLE FOR ALL INSPECTION REQUIREMENTS UNLESS OTHERWISE SPECIFIED HEREIN.

4.2 QUALIFICATION INSPECTION: QUALIFICATION TESTS SHALL NOT BE PERFORMED BY THE MANUFACTURER UNLESS REQUESTED BY THE PURCHASER. HOWEVER, THE PURCHASER RESERVES THE RIGHT TO INSPECT ALL PARTS AGAINST THIS DOCUMENT AND TABLE III OF MIL-T-23648.

4.3 QUALITY CONFORMANCE INSPECTION

4.3.1 GROUP A INSPECTION: GROUP A INSPECTION SHALL BE IN ACCORDANCE WITH TABLE IV OF MIL-T-23648 EXCEPT DCR VS APPLIED CURRENT OF 3.0 AMP. (PER TABLE I) SHALL BE SUBSTITUTED FOR RESISTANCE RATIO CHARACTERISTICS.

4.3.2 GROUP B AND C INSPECTION: ONLY WHEN CALLED OUT IN THE PURCHASE ORDER OR CONTRACT SHALL THE SUPPLIER PERFORM THE GROUP B AND C INSPECTION TESTS OF MIL-T-23648.

5.0 DIMENSIONAL DATA IS BASED ON AMERICAN NATIONAL STANDARD ANSI Y14.5M-1982.

6.0 SUGGESTED SOURCE(S) OF SUPPLY:

6.1 KETEMA/RODAN DIV
ANAHEIM, CA
FSCM NO: 15454
MANUFACTURER'S PART NO.: 56220-5

7.0 "IDENTIFICATION OF THE SUGGESTED SOURCE(S) OF SUPPLY HEREON IS NOT TO BE CONSTRUED AS A GUARANTEE OF PRESENT OR CONTINUED AVAILABILITY AS A SOURCE OF SUPPLY FOR THE ITEM(S)."

DAAB07-84-C-D001

SIZE	FSCM NO.	DWG. NO.
A	80063	A3029311
SCALE	2/1	LTR 8 SHEET 4

1 Jul 82

DAAB-07 Form 01-1

DAAB-07 1467-1-82

[illegible][illegible][illegible]

23